

Model	Heating Capacity		Dimensions (cm)			Out flow return flange	chimney	Operatio n weight
TYPE	Kcal/hr	Btu/hr	Width	Height	Length	Inch	cm	Kg
S.M.D-10	100.000	400.000	85	105	130	2	15	800
S.M.D-15	150.000	600.000	100	125	160	2	20	1150
S.M.D-20	200.000	800.000	100	125	170	3	20	1500
S.M.D-25	250.000	1.000.000	105	135	175	3	20	1620
S.M.D-30	300.000	1.200.000	105	140	190	4	20	1800
S.M.D-40	400.000	1.600.000	120	155	205	4	25	2350
S.M.D-50	500.000	2.000.000	135	165	210	4	25	2650
S.M.D-60	600.000	2.400.000	135	175	230	4	25	3300
S.M.D-70	700.000	2.800.000	135	175	260	4	30	3700
S.M.D-80	800.000	3.200.000	140	180	270	4	30	4150
S.M.D-90	900.000	3.600.000	145	190	290	5	35	4800
S.M.D-100	1.000.000	4.000.000	150	190	300	5	35	5600
S.M.D-125	1.250.000	5.000.000	150	200	325	5	35	6300
S.M.D-150	1.500.000	6.000.000	170	215	350	5	35	7000
S.M.D-175	1.750.000	7.000.000	180	225	350	6	35	8800
S.M.D-200	2.000.000	8.000.000	200	235	380	6	40	11000