

TYPE		B.G.T 250	B.G.T 500	B.G.T 1000	B.G.T 1500	B.G.T 2000	B.G.T 3000	B.G.T 5000	B.G.T 7000	B.G.T 8000	B.G.T 10000	B.G.T 12000	B.G.T 14000
HEATING Capacity	Kcal/hr	155000	310000	620000	930000	1240000	1860000	3100000	4340000	4960000	6200000	7440000	8680000
	Lbs/hr	550	1100	2200	3300	4400	6600	11000	154000	17600	22000	26400	30800
	Kg/hr	250	500	1000	1500	2000	3000	5000	7000	8000	10000	12000	14000
Fuel oil consume	Lit/hr	16	31	70	102	121	180	270	420	490	609	825	960
Fuel Gas consume	M3/hr	14	26.5	61	89	105	159	201	378	429	519	730	885
Dimension cm	Length	170	220	260	300	315	400	490	500	550	600	610	650
	Wide	140	170	190	190	210	240	260	290	310	350	390	410
	Hight	140	165	200	200	230	250	270	320	335	380	410	430
Steam outlet	Inch	1.1/2	2	2.1/2	2.1/2	3	4	5	6	7	7	8	8
Water Inlet	Inch	1	1	1	1	1	1	1.1/2	2	2	2.1/2	2.1/2	2.1/2
Heating Surface	M 2	6	11	22	33	46	65	105	146	175	205	260	295
Transport Weight	Ton	1.4	2.3	3.8	4.5	5.2	7	11.5	15.5	17.5	22	24.5	28

1Kcal/hr=3.93 Btu/hr , 1 bar = 14.5 Psi 1 Atm = 1.013 bar 1 Mw = 1000 Kw =860 000 Kcal/hr